

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
**E-7481**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL  GAS WELL  OTHER- **Water Injection Well**

7. Unit Agreement Name  
**Flying "M" (SA) Unit** *Jan 19*

2. Name of Operator  
**Coastal States Gas Producing Company**

8. Farm or Lease Name  
**Flying "M" San Andros**

3. Address of Operator  
**P. O. Box 235, Midland, Texas 79701**

9. Well No.  
**10-2**

4. Location of Well  
UNIT LETTER **L** **485** FEET FROM THE **west** LINE AND **1980** FEET FROM THE **south** LINE, SECTION **22** TOWNSHIP **9S** RANGE **33E** N.M.P.M.

10. Field and Pool, or Wildcat  
**Flying "M" (SA)**

15. Elevation (Show whether DF, RT, GR, etc.)  
**4351 GR**

12. County  
**Lea**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK   
TEMPORARILY ABANDON   
PULL OR ALTER CASING   
OTHER

PLUG AND ABANDON   
CHANGE PLANS

REMEDIAL WORK   
COMMENCE DRILLING OPNS.   
CASING TEST AND CEMENT JQB   
OTHER

ALTERING CASING   
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Give New Mexico Oil Conservation Commission, Hobbs office, 24 hours prior notice before setting first plug.
2. Pull and lay down tubing.
3. Spot 100' cement plug on bottom. Allow 12 hours WOC. Tag top of plug.
4. Determine free point, cut off and plug recoverable casing.
5. Mud up between all plugs with 25 sx. salt gel/100 bbl. brine mixture.
6. Spot 100' cement plug in and out of casing stub.
7. Spot 100' cement plug from top of salt at approximately 2020'.
8. Spot 100' cement plug in and out of surface casing bottomed at 264'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J. B. Shepherd* TITLE **District Production Manager** DATE **2-26-74**

APPROVED BY *Joe O. Bailey* TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: