

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-025-31018

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
V-2722

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
Remuda State Unit

1. Type of Well:
OIL WELL GAS WELL OTHER

8. Well No.
2

2. Name of Operator
YATES PETROLEUM CORPORATION

9. Pool name or Wildcat
Flying M San Andres

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line
Section 8 Township 10S Range 33E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4199' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: Production Csg, Perforate, Treat <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
TD 4565'. Reached TD 10-19-90. Ran 108 joints 5-1/2" 15.5# J-55 LT&C casing set 4565'. Guide shoe set 4565'. Float collar set 4522'. Marker joint set 4374'. Cemented w/500 gals Super Bond 102, 450 sx "C" w/4%/sx Salt, .3% CF-22 (yield 1.32, wt 14.8). PD 1:15 AM 10-20-90. Bumped plug to 1500 psi, held okay. WIH and perforated 4390-4410' w/11 - .40" holes as follows: 4390, 91, 94, 96, 97, 98, 4403, 04, 05, 09, 4410'. Acidized perms 4390-4410' w/1000 gals 15% NEFE and 20 ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 11-8-90
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: