



LOCATE WELL CORRECTLY

U. S. LAND OFFICE LC
SERIAL NUMBER 260177
LEASE OR PERMIT TO PROSPECT PROSPECT

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

JUN 22 1960

HOBBS, NEW MEXICO

LOG OF OIL OR GAS WELL

Company L. R. French, Jr. Address P. O. Box 591, Odessa, Texas
Lessor or Tract Federal Field Bluitt State New Mexico
Well No. 1 Sec. 13 T 8-S R. 36-E Meridian NMPM County Roosevelt
Location 554 ft. N of S Line and 554 ft. E of E Line of Section 13 Elevation 4073 DF
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed L. H. Reynolds

Date June 20, 1960

Title PRODUCTION SUPERINTENDENT

The summary on this page is for the condition of the well at above date.

Commenced drilling April 26, 1960, 19... Finished drilling June 8, 1960, 19...

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 9644 to 9668 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from Undetermined to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From-	To-	
13-3/8	48#	8	J&L	410	PT. P.				Surface
8-5/8	32#	8	J&L	9648	Lock				Salt String
5-1/2	17#/Ft.	8	J&L	9680	Lock	9648	9668		Oil Zone

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
13-3/8	410	400	Plug	---	---
8-5/8	4145	500	Plug	---	---
5-1/2	9680	300	Plug	---	---

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 9680 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

Put to producing June 16, 19 60

The production for the first 24 hours was 480 barrels of fluid of which 100% was oil; _____% emulsion; _____% water; and _____% sediment.

Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

J. L. Appertout, Driller
W. H. Rains, Driller
C. C. Carney, Driller
Woodrow Green, Driller
Tool Pusher

FORMATION RECORD

FROM-	TO-	TOTAL FEET	FORMATION
Surface	2265	2265	Red Beds
2265	2854	589	Salt
2854	2957	103	Sand (Top Yates 2854')
2957	3497	540	Anhydrite and Salt
3497	4060	563	Anhydrite, Red Bed & Salt (Top San Andres 4060)
4060	5515	1455	Lime, Anhydrite & Salt (Top Glorieta 5515)
5515	6186	671	Sand, Salt & Lime (Top Clearfork 6186)
6186	6934	748	Lime w/salt stringers (Top Tubb 6934)
6934	7752	818	Lime, Sand & Shale (Top Abo 7752)
7752	9680	1928	Lime w/shale streaks (Top Wolfcamp 9072)
TD	9680	9680	Top Penn. 9566 Top Bough "C" 9644'

