

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE O. C. C.  
NEW MEXICO OIL CONSERVATION COMMISSION

JUN 13 9 16 AM '68

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
**SG & FC # CS-1**

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Taylor Pruitt</b>	8. Farm or Lease Name <b>HSG</b>
3. Address of Operator <b>c/o Oil Reports &amp; Gas Services, Box 763, Hobbs, New Mexico</b>	9. Well No. <b>3</b>
4. Location of Well UNIT LETTER <b>J</b> 1980 FEET FROM THE <b>South</b> LINE AND 1980 FEET FROM THE <b>East</b> LINE, SECTION <b>26</b> TOWNSHIP <b>7S</b> RANGE <b>32E</b> NMPM.	10. Field and Pool, or Wildcat <b>Chaveroo San Andres</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4458.5 GR</b>	12. County <b>Roosevelt</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**Spudded 12 1/4" hole 1:30 PM 5/21/68. Cemented 8 5/8" 20# casing at 343 feet with 225 sacks Class "H", 2% calcium chloride. Cement circulated. Plug down 7:15 PM 5/21/68. WOC 18 hours and tested casing with 1000# for 30 minutes, test O.K.**

**Cemented 5 1/2" 14.0# & 15.5# J-55 casing at 4499 feet with 300 sacks Halliburton light cement and 350 sacks Incor Pemmix, 2% gel, 0.75% CFR-2, 11# salt per sack. Plug down 5:30 PM 5/29/68. WOC 48 hours and tested casing with 1500# for 30 minutes, test O.K.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *H. J. Smith* TITLE Agent DATE 6/13/68

APPROVED BY *[Signature]* TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: