

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-15019

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cone Federal

9. WELL NO.

5 6

10. FIELD AND POOL, OR WILDCAT

Tomahawk, San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 30, T7S, R32E

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
SUNDANCE OIL COMPANY

3. ADDRESS OF OPERATOR
Suite 510, 1776 Lincoln St., Denver, CO 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL, 660' FWL Unit M

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4411' GI

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SET SURFACE CASING

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XXX

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 1:15 p.m. 11/3/78. Drilled 12 1/4" surface hole to 1770'. Ran 45 jts., 22.36#, 8 5/8" surface casing. Landed at 1768'. Cemented w/400 sx B-J light mixed w/5# Gilsonite, 1/4# Cello Flakes, 2% CaCl followed by 200 sx Class C, 2% CaCl. Plug down at 11 a.m. 11/5/78. Pressured to 900# for 10 minutes, okay. Circulated 50 sx. WOC 17 hrs. Nippled up BOP, tested to 1000# for 30 minutes, held okay.

RECEIVED
NOV 8 1978
U.S. GEOLOGICAL SURVEY
DENVER, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard O. Dimit

TITLE

Vice President, Production

DATE

11/6/78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
NOV 8 1978
U.S. GEOLOGICAL SURVEY
DENVER, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

1914

U. S. DEPARTMENT OF AGRICULTURE
WASHINGTON, D. C.