

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
SUNDANCE OIL COMPANY

3. ADDRESS OF OPERATOR
Suite 510, 1776 Lincoln St., Denver, CO 80203

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL, 1980' FEL, Unit B
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) SET PRODUCTION CASING <input type="checkbox"/>	<input type="checkbox"/>

RECEIVED

JUN 11 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
NM-15019

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Cone Federal

9. WELL NO.
11

10. FIELD OR WILDCAT NAME
Tomahawk, San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 31, T.7S., R.32E.

12. COUNTY OR PARISH
Roosevelt

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4437' GL, 4449' KB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to total depth of 4340'. Ran Sidewall Neutron Porosity log. Ran 113 jts. 4 1/2", 10.5#, K-55 casing. Set at 4336'. Cemented with 300 sx 50/50 Pozmix mixed with 2% gel, 8# salt, 1/4# Celloflakes. Plug down at 9 a.m. 6/6/79. Pressured up to 1500#, okay. Released rig at 10:30 a.m. 6/6/79. WOCU.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimit TITLE VP, Production DATE June 7, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
JUN 11 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JUN 12 1979

**OIL CONSERVATION COMM.
HOBBS, N. M.**