



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 02109
Unit Las Cruces "A"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL <u>WELL</u>	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 16, 1955

Well No. 1 is located 660 ft. from N line and 1980 ft. from W line of sec. 27

NE/4 NW/4 Sec. 27
(¼ Sec. and Sec. No.)

13S
(Twp.)

31E
(Range)

N.M.P.M.
(Meridian)

Drickey Queen
(Field)

Chaves County
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ? ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To be drilled with rotary tools from surface to total depth of 3050' in the Queen Sand. Casing program to be as follows:

SIZE HOLE	SIZE CASING	APPROX. CASING POINT	SACKS CEMENT
18"	13-3/8"OD	150'	135
11"	8-5/8"OD	1450'	none
7-7/8"	5-1/2"OD	3000'	200

The Halliburton process will be used in cementing all casing and cement will be circulated to surface on the 13-3/8"OD casing. The 8-5/8"OD casing will be landed, mudded and pulled.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Skelly Oil Company

Address P.O. Box 38

Hobbs, New Mexico

By [Signature]

Title Dist. Supt.