

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
K-5919

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Lea-State
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER N , 660 FEET FROM THE south LINE AND 1980 FEET FROM THE west LINE, SECTION 25 TOWNSHIP 13S RANGE 32E NMPM.	10. Field and Pool, or Wildcat Baum Upper Penn, North
15. Elevation (Show whether DF, RT, GR, etc.) 4300.4' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well @ 7:30 P.M. 1-15-80 by Hondo Drlg. Co. Rig #1. Drill 17½" hole to 360'.
Ran 13 3/8" 48# H-40 ST&C csg. set @ 360'. Cement w/200 sx. Class "C" cement
w/¼# Flocele/sx, 2% calcium chloride + 200 sx. Class "C" w/2% calcium chloride.
Plug down @ 11:30 A.M. 1-16-80. Circ. 10 sx. to surface. WOC 18 hrs. Nipple up BOP.
Test csg. and BOP to 1000# for 30 min. Hold O.K.
Drill ahead 11" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *C. Harvey* TITLE District Engineer DATE 1-21-80

APPROVED BY Jerry Sexton TITLE _____ DATE JAN 23 1980
Dist. I, Supv.

CONDITIONS OF APPROVAL, IF ANY: