

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-041-20514

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.
L-5048

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER
Name of Operator
Phillips Petroleum Company
Address of Operator
Room 401, 4001 Penbrook Street, Odessa, Texas 79762
Location of Well
UNIT LETTER H 1980 FEET FROM THE North LINE AND 510 FEET FROM
THE East LINE, SECTION 36 TOWNSHIP T-5-S RANGE R-32-E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Lambirth - State
9. Well No.
1
10. Field and Pool, or Wildcat
Peterson Fusselman South
12. County
Roosevelt

15. Elevation (Show whether DF, RT, GR, etc.)
4400 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER
PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
COMMENCE DRILLING OPNS.
CASING TEST AND CEMENT JOB
OTHER Total Depth
ALTERING CASING
PLUG AND ABANDONMENT

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 11-17-79 MI Rial Drlg. Spudded @ 2:00 P.M. w/17-1/2" bit drld to 358'. Ran 13-3/8", 48#, H-40 STC csg set @ 358'. Cmt w/420 sxs C1 "H" (15.8 ppg) w/2% CaCl, 1/4# Flocele. Plug to 330' w/51 BW max psi 300#. Circ 96 sxs. WOC 14 hrs. Temp of cmt 56°, zone temp 63°, estimate strength exceeds 500 psi, cmt in place 14 hrs before testing.
- 11-18-79 Test BOP & csg. OK. Drld plug, cmt & 10' of formation. Drld ahead w/11" hole.
- 11-22-79 Ran 8-5/8", 24#, K-55 csg set @ 3500'. Cmt w/850 sxs C1 "H" w/30% DD, tailed in w/200 sxs C1 "H", w/2% CaCl. Circ 160 sxs to pit. WOC 18 hrs. NU BOP's.
- 11-23-79 Tested BOP's & csg. OK. Drld ahead w/7-7/8" hole.
- 12-9-79 Reached TD 7971'. Circ to run open hole logs.
- 12-15-79 Set 216 jts 5-1/2", 14#, F 15.5#, K-55, LTC A STE csg @ 7971'. Baker Float collar 7935'. B-J cmt w/400 sxs C1 "H" w/30% D.D. + 2% KCl + 0.8% D-19 + 1/2# Celoflakes tailed w/300 sxs C1 "H" + 2% KCl + 1% D-19. Plug to 7935' w/10 bbls 10% Acetic acid + 180 FW maxi PSI 750#. Bump plug w/2250#. Run temp survey TOC 5100'. Job complete 1:20 P.M., 12-14-79. WOC 6 hrs. Release rig 11:00 P.M., 12-14-79. Prep to complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed by W. J. Mueller TITLE Sr. Engineering Specialist DATE December 17, 1979

APPROVED BY Jerry Sexton TITLE Dist. 1. Supv. DATE _____

CONDITIONS OF APPROVAL, IF ANY