

|                               | O. D. | I. D.  | LENGTH | DEPTH |
|-------------------------------|-------|--------|--------|-------|
| Drill Pipe or Tubing          |       |        |        |       |
| Drill Collars                 |       |        |        |       |
| Reversing Sub                 | 6.00" | 3.00"  | 1.00'  |       |
| Water Cushion Valve           |       |        |        |       |
| Drill Pipe                    | 4.50" | 3.826" | 7936'  |       |
| Drill Collars                 | 6.00" | 2.25"  | 531'   |       |
| Handling Sub & Choke Assembly |       |        |        |       |
| Dual CIP Valve                |       |        |        |       |
| Dual CIP Sampler              | 5.00" | .75"   | 7.50'  | 8475' |
| Hydro-Spring Tester           | 5.00" | .75"   | 4.00'  | 8479' |
| Multiple CIP Sampler          |       |        |        |       |
| Extension Joint               |       |        |        |       |
| AP Running Case               | 5.00" | 3.75"  | 5.00'  | 8484' |
| Hydraulic Jar                 | 5.00" | 1.75"  | 5.00'  |       |
| VR Safety Joint               | 5.00" | 1.00"  | 3.00'  |       |
| Pressure Equalizing Crossover |       |        |        |       |
| Packer Assembly               | 7.75" | 1.53"  | 6.00'  | 8496' |
| Distributor                   | 5.00" | 1.68"  | 2.00'  |       |
| Packer Assembly               | 7.75" | 1.53"  | 6.00'  | 8504' |
| Flush Joint Anchor            |       |        |        |       |
| Pressure Equalizing Tube      |       |        |        |       |
| Blanked-Off B.T. Running Case |       |        |        |       |
| Drill Collars                 |       |        |        |       |
| Anchor Pipe Safety Joint      |       |        |        |       |
| Packer Assembly               |       |        |        |       |
| Distributor                   |       |        |        |       |
| Packer Assembly               |       |        |        |       |
| Anchor Pipe Safety Joint      | 5.75" | 1.50"  | 4.00'  |       |
| Side Wall Anchor              |       |        |        |       |
| Drill Collars                 |       |        |        |       |
| Flush Joint Anchor            | 5.75" | 2.87"  | 22'    |       |
| Blanked-Off B.T. Running Case | 5.75" | 2.50"  | 6.00'  | 8532' |
| Total Depth                   |       |        |        | 8538' |