

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

FORM APPROVED  
BUDGET BUREAU NO. 42-R1424

COPY TO O. C. G.

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 057210

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER  INJECTION WELL

7. UNIT AGREEMENT NAME

MCA

2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY

8. FARM OR LEASE NAME

MCA UNIT

3. ADDRESS OF OPERATOR  
BOX 460 HOBBS, NEW MEXICO 88240

9. WELL NO.

207

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

10. FIELD AND POOL, OR WILDCAT

MALJ. G-SA REPRESS

660' FSL AND 660' FEL OF SEC 28

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 28 T17S-R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3954' DF

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEX

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4 1/2", 10.23# LINGER SET AT 3858'. CEMENTED WITH 130 SACKS CLASS "C" CEMENT W/ 3/4 OF 1% CFR-2, 3# SALT PER SACK, 3# SAND PER SACK & 1/4# FLOCELE PER SACK. CEMENT TO SURFACE AFTER CIRCULATION. TOC 50' BELOW SURFACE. DRILLED OUT CEMENT TO 4125'. SET PACKER AT 3809' AND RETURNED WELL TO INJECTION.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE ADMIN. SUPERVISOR

DATE 4-5-72

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

USGS (5)  
MCA (3)  
FILE

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD  
APR 7 1972  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

RECEIVED

APR 11 1951

OIL CONSERVATION BOARD  
HOUSTON, TEXAS