

**DUPLICATE**

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 APR 20

AM 7:36

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<b>X</b>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 19, 1954  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Oil Company  
(Company or Operator)

Pacific Royalty  
(Lease)

Ralph Johnson  
(Contractor)

Well No. 4 in the NE 1/4 SE 1/4 of Sec. 10

T. 15-S, R. 37-E, NMPM, Denton Pool, Lea County.

The Dates of this work were as follows: April 1 thru April 17, 1954

Notice of intention to do the work (was) ~~submitted~~ submitted on Form C-102 on March 24, 1954,  
(Cross out incorrect words)

and approval of the proposed plan (was) ~~obtained~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Plugged and abandoned Pacific Royalty No. 4 as follows:

- (1) Hole was loaded with mud when testing was completed on March 21, 1954
- (2) Shot and pulled 10,414 feet of 7" casing
- (3) Ran Baker Type C bridging plug and set at 9675 feet. Dumped 75 gallons pea gravel on top and followed with 44 gallons of Cal Seal. Found top of plug at 9645 feet. Bridge holding OK. Spotted 200 sacks of cement from 9630 feet. Circulated and hole remained full all the way. Pulled tubing free. Checked top of plug at 8993'.
- (4) Pulled tubing to 4770 feet and spotted 20 sack cement plug.
- (5) Pulled to surface and spotted 10 sack cement plug. Erected 4" x 4" marker as required by Rule 202. WELL PLUGGED & ABANDONED 4-17-54.

Witnessed by: H. G. Starling (Name) Shell Oil Company (Company) Production Foreman (Title)

Approved: OIL CONSERVATION COMMISSION

*H. G. Starling*  
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: F. D. Leigh (Original signed by F. D. Leigh)

Position: Division Mechanical Engineer

Representing: Shell Oil Company

Address: Box 1957, Hobbs, New Mexico

(Title)

(Date)

