

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> WIW	7. Unit Agreement Name
2. Name of Operator Mobil Oil Corporation	8. Farm or Lease Name E-K Queen Unit Tr. 2
3. Address of Operator P. O. Box #633, Midland, Texas	9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> . <u>1980</u> FEET FROM THE <u>south</u> LINE AND <u>1897</u> FEET FROM THE <u>west</u> LINE, SECTION <u>19</u> TOWNSHIP <u>18S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat E-K Yates 7 Rivers Queen
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Convert to WIW</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4704 TD. 4471 Baker BP. Queen perms (4432-4444).  
6/16/66. MIRU Well Service Pole Unit. Clean out. Pull tbg. Dmp 1 sx cement on BP at 4474. Plug back to 4464. Ran 1 6' pc of 2-3/8" fiber glass tbg and Guiberson "Shorty" tension pkr on 2-3/8" cement lined tbg to 4391. Pkr set at 4385 w/ 14,000# tension. Install Injection head. Completed as WIW 6/22/66.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Authorized Agent DATE 7/25/66

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_