

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

7. Unit Agreement Name

Name of Operator

N. HOBBS (G/SA) UNIT

SHELL OIL COMPANY

8. Farm or Lease Name

Address of Operator

SECTION 13

P. O. BOX 991, HOUSTON, TX 77001

9. Well No.

Location of Well

141

UNIT LETTER M 660 FEET FROM THE SOUTH LINE AND 660 FEET FROM

10. Field and Pool, or Wildcat

THE WEST LINE, SECTION 13 TOWNSHIP 18-S RANGE 37-E NMPM.

HOBBS (G/SA)

15. Elevation (Show whether DF, RT, GR, etc.)

12. County

3684' DF

LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING

PLUG AND ABANDON
CHANGE PLANS

REMEDIAL WORK *
COMMENCE DRILLING OPNS.
CASING TEST AND CEMENT JOB

ALTERING CASING
PLUG AND ABANDONMENT

OTHER

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 10-3-81: CO to 3900'. Set RBP @3880'. Pressure tested RBP, 7" csg, and tbg to 500 psi-- held OK. Spotted 3 sx 20-40 mesh sand on top.
- 10-6-81: Perf'd 7" csg @2666' - 2667'.
- 10-7-81: Spotted 10 bbls 15% HCL acid on bottom @2685'. Reperforate @2666' - 2667'.
- 10-9-81: Set CICR @2537'. Pumped 1500 sx Class "C" cmt and 10# salt/sx. WOC 24 hrs.
- 10-10-81: Ran temp survey. TOC @2000'. Perf'd squeeze holes @1905'. Set pkr @1889' w/ 15,000# tension. Set CICR @1736'. Spotted 10 bbls 15% HCL acid. Pumped 500 sx Class "C" cmt.
- 10-11-81: Ran temp survey. TOC @1600'.
- 10/13-16/81: Tagged cmt @1725'. Drld cmt to 1736' - top of CICR - to 2027'. Pressure tested squeeze holes @1905' - held OK. Ran bit to 2514'. Tagged cmt and drld cmt to 2544'.
- 10/17-18/81: Drld cmt 2544' to 2840'. Pressure tested squeeze holes @2666' - 2667' to 500 psi for 30 minutes - held OK.
- 10-21-81: Retrieved bridge plug.
- 10-22-81: Well completed and returned to temporarily abandoned status.

* PER NEW MEXICO OIL CONSERVATION COMMISSION REQUEST

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Adrie Cortez for A. J. FORE TITLE SUPERVISOR REG./PERMITTING DATE NOVEMBER 11, 1981

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NOV 16 1981