

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Testing well (Other) for casing leaks	

September 22, 1953
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Service Oil Co. Hobbs
(Company or Operator) (Lease)

Cities Service Oil Co. Well No. 1 in the 1/4 Sec. 19
(Contractor)

T. 18, R. 38, NMPM, Hobbs, Lea County.

The Dates of this work were as follows: 9-8-53 and 9-9-53

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____.
(Cross out incorrect words)

and approval of the proposed plan (was) ~~was not~~ obtained. (Work ordered by Oil Conservation Commission)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Shut well in for 25 hrs and 30 min and ran BHP test. Left well had been shut in for 27 hrs ran static temperature survey at 25' from 0 to 4000'. (2 copies of temperature survey attached)

Tested surface connections for casing leaks; 49 hr. shut in pressures - 12 1/2" - 9" was 2, 9" - 6 5/8" was 315, 6 5/8" - 3" was 1005, 3" tubing was 180'.

Opened or closed between 12 1/2" and 9", street gas filed off immediately. Opened between 9" and 6 5/8", blew down street gas in 15 min then closed.

Drawdown pressures: 12 1/2" - 9" was 0, 9" - 6 5/8" was 0, 6 5/8" - 3" was 1005, 3" tubing was 180'. No casing leaks indicated.

Witnessed by: R. P. Hemphill Cities Service Oil Co. Asst. Prod. Foreman
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Raymond M. Rogers

Position: Production Engineer

Representing: Cities Service Oil Co.

Address: Box 97, Hobbs, New Mexico

Engineer District 1

OCT 6 1953

