

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-025-07465

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT'  
(FORM C-101) FOR SUCH PROPOSALS)

7. Lease Name or Unit Agreement Name

H.D. MCKINLEY

1. Type of Well:  
OIL WELL  GAS WELL  OTHER TA'D

8. Well No.

5

2. Name of Operator  
AMERADA HESS CORPORATION

9. Pool name or Wildcat

BOWERS SEVEN RIVERS

3. Address of Operator  
DRAWER D, MONUMENT, NM 88265

4. Well Location

Unit Letter F : 1909 Feet From The WEST Line and 1980 Feet From The NORTH Line

Section 30 Township 18S Range 38E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3662' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK  PLUG AND ABANDON   
TEMPORARILY ABANDON  CHANGE PLANS   
PULL OR ALTER CASING   
OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK  ALTERING CASING   
COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
CASING TEST AND CEMENT JOB   
OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-18 THRU 5-19-93

MIRU POOL WELL SER. PU & WELL PLUGGING EQUIP. INSTALLED BOP & TOH W/TBG. RAN A ELDER 5-1/2" CIBP & SET AT 3050'. DISPLACED HOLE W/75 BBLs. 9.5# MUD. SPOTTED 25 SK. CEMENT PLUG FROM 3050' TO 2800'. PULLED & LAID DOWN 38 JTS. 2-3/8" TBG. & SPOTTED 25 SK. CEMENT PLUG FROM 1850' TO 1600'. PULLED & LAID DOWN 52 JTS. 2-3/8" TBG & SPOTTED 25 SK. CEMENT PLUG FROM 250' TO SURFACE. FINISHED TOH W/TOTAL 98 JTS. 2-3/8" TBG. & SETTING TOOL. REMOVED BOP, CUT OFF WELLHEAD & INSTALLED DRY HOLE MARKER. RDPU & CUT OFF ANCHORS. WELL PLUGGED & ABANDONED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler Jr TITLE SUPV. ADM. SVC. DATE 5-20-93

TYPE OR PRNT NAME R.L. WHEELER, JR. TELEPHONE NO. (505) 393-2144

(This space for State Use)

APPROVED BY Cary W. Hill TITLE OIL & GAS INSPECTOR DATE SEP 20 1993

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
JULY 24 1980  
120 HOBBS OFFICE