

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State  Fee   
5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name South Hobbs (GSA) Unit
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 5
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> <u>660</u> FEET FROM THE <u>East</u> <u>33</u> LINE, SECTION <u>18-S</u> TOWNSHIP <u>38-E</u> RANGE <u>38-E</u> NMPM.	10. Field and Pool, or Acrecat Hobbs GSA
15. Elevation (Show whether DF, RT, GR, etc.) 3531' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to cement squeeze water productive zone as follows:

Pull tubing and pump. Set a cast iron bridge plug at approx. 4044' and set a cement retainer at approx. 3900'. Squeeze perforations 3994'-4038' with 25 sacks class C neat cement followed by 100 sacks class C with 10# Gilsonite per sack of cement. Tail in with 100 sacks class C neat. Sting out of cement retainer and reverse out excess cement. Drill out cement retainer and cement to 4038'. Pressure test squeezed perforations. Drill out cast iron bridge plug. Run 2-7/8" tubing and downhole gas separator with seating nipple above the separator, landing at approx. 4030'. Pump test and return well to production.

0+4-NMOCD,H 1-HOU 1-SUSP 1-CLF

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cathy R. Forman TITLE Assist. Admin. Analyst DATE 8-12-82

ORIGINAL SIGNED BY JERRY SEXTON TITLE \_\_\_\_\_ DATE AUG 16 1982

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL DISTRICT 1 SUPR.

5

RECEIVED  
AUG 13 1982  
C.C.D.  
HOBBS OFFICE