

COUNTY	WY	FIELD	Lusk	STATE	WY
OPR	U. S. SMELTING, REFG. & MINING CO.				MAP
1 Lusk-State					
Sec. 32, T-18-S, R-32-E				CO-ORD	
660' fr S & W Lines of Sec.					
Spd 4-22-65					
Cmp 6-5-65					
		CLASS		E	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Strwn 11264			
		Reef 11390			
		B/Rf 11556			
13 3/8"	645'	510			
8 5/8"	3211'	900			
5 1/2"	11600'	375			
LOGS	EL	GR	RA	IND	HC A
		TD 11600', PBD 11500'			

IP Strawn Perfs 11396-476' Flwd 336 BOPD. Pot. Based on 24 hr test thru 16/64" chk., TP 990#, CP Pkr, Gravity 47.

Distribution limited and publication prohibited by subscribers' agreement.  
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 11,500' TYPE  
 DATE

F.R. 4-22-65; Oper's Elev. 3693' KB  
 PD 11,500' - Strawn  
 4-26-65 Drlg. 2790' anhy.  
 5-3-65 Drlg. 5108' lm.  
 5-10-65 Drlg. 8342' im & sd.  
 5-17-65 Drlg. 10817'.  
 5-24-65 TD 11600', WCC.  
 6-1-65 TD 11600', prep to swab.  
 Perf 11520-540'  
 Ac. 3000 gals.,  
 Swbd dry.  
 Re-Perf 11520-540'  
 Re-Ac. 3000 gals.  
 6-7-65 TD 11600', PBD 11500', SI for Storage.  
 Swbd dry (11520-540')  
 Set BP @ 11500'

LEA Lusk NM Sec. 32-18S-32E  
U. S. SMELTING, REFG. & MINING CO., #1 Lusk-State  
Page #2

6-7-65 Continued  
Perf 11396-436'  
Ac. 2500 gals.,  
Perf 11470-476',  
Ac. 2500 gals.,  
Flwd 336 BNO in 24 hrs thru 1/2" chk.,  
TP 1200-990# (11396-476')  
6-14-65 TD 11600', PBD 11500', COMPLETED.