

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
NM-2056

7. Unit Agreement Name

8. Farm or Lease Name
Graham State (NCT-A)

9. Well No.
5

10. Field and Pool, or Wildcat
Undesignated

12. County
Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER-

2. Name of Operator
Gulf Oil Corporation

3. Address of Operator
Box 670, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER **H** **1980** FEET FROM THE **North** LINE AND **760** FEET FROM
THE **East** LINE, SECTION **24** TOWNSHIP **18-S** RANGE **37-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| | | | |
|--|---|--|---|
| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | OTHER <input type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 17-1/2" hole at 3:30 PM, March 24, 1969. Drilled to 412'. Ran 12 joints, 393' of 13-3/8" OD 48# H-40 ST&C casing set and cemented at 408' with 400 sacks of Class C cement with 2% Ca Cl2. Cement circulated. WOC & NU 18 hours. Tested casing with 1150#, 30 minutes. OK.

Started drilling 11" hole at 412'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. D. BORLAND ORIGINAL SIGNED BY C. D. BORLAND TITLE Area Production Manager DATE March 26, 1969

APPROVED BY [Signature] TITLE SUPERVISOR DATE

CONDITIONS OF APPROVAL, IF ANY: