

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-26929

5a. Indicate Type of Lease

State Fee

5. State Oil & Gas Lease No.

B-1502

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name East Vacuum Gb/SA Unit
2. Name of Operator Phillips Petroleum Company		8. Farm or Lease Name East Vacuum Gb/SA Unit Tr 0524
3. Address of Operator Room 401, 4001 Penbrook Street, Odessa, Texas 79762		9. Well No. 002
4. Location of Well UNIT LETTER <u>C</u> <u>950</u> FEET FROM THE <u>North</u> LINE AND <u>1350</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Vacuum Gb/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3959.8' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER

PLUG AND ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIATION WORK

COMMENCE DRILLING OPS.

CASING TEST AND CEMENT JOB

OTHER total depth

ALTERING CASING

PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 8-24-80 MI Marc Drlg. Spudded w/12-1/4" bit to 350'. Ran 9-5/8" 32#, J-55 csg set at 349'. Cmtd w/400 sxs Cl "H" w/2% CaCl₂, 1/4#/sxs Flocele. Circ 70 sxs to surface. Tstd csg 14 hrs after plugdown. Temp of cmt 65°, formation temp in zone 65° cmt strength at time of csg test, 71,000 psi, time cmt in place prior to test, 14 hrs. Tstd csg & BOP 1000#, O.K. Drl'd ahead w/8-3/4" bit.
- 9-9-80 Drl'd to 4800 TD. Logged.
- 9-10-80 Ran 7", 23#, K-55 csg set @ 4800'. Cmtd w/770 sxs TLW w/12# sxs salt, 10% DD, 1/4# sxs Flocele, 3#/sxs Gilsonite, followed w/450 sxs Cl "H" w/8 # sxs salt; circ 110 sxs to surface.
- 9-11-80 Released rig; prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Senior Engineering Specialist DATE September 12, 1980

Orig. Signed by

Jerry Sexton

Dist. L. Sign

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

brb