

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other WIW

2. NAME OF OPERATOR  
Sun Exploration and Production Co.

3. ADDRESS OF OPERATOR  
P.O. Box 1861, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit Ltr. "N" S  
AT TOP PROD. INTERVAL: 660' FSL & 1980' FWL  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Deepened through Seven Rivers		

5. LEASE  
**MM-025497**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Jennings B Federal

9. WELL NO.  
2

10. FIELD OR WILDCAT NAME  
Northeast Lusk Yates / *Seven Rivers*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15, T-19-S, R-32-E

12. COUNTY OR PARISH 13. STATE  
Lea | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- MIRU. Install BOP. Rise Otis Perma-latch pkr at 2889' and POH w/2-3/8" cmt lined tbg.
- RIH w/4-3/4" RB & 8 - 3 1/2" DC's on 2-7/8" WS. Deepen well from 3065 (PBD) to 3350'±. (As recommended by Geol. & Engr.). Circ hole c/n w/prod. wtr. POH.
- RIH w/5 1/2" RDG pkr on 2-7/8" WS w/9 jts. tailpipe. Spot 5 bbls 15% NEHCL from 3350'-3122'. Raise and set pkr at 2820'±, tailpipe at 3100'±. Trap 500 psi on annulus.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dee Ann Kemp TITLE Associate Acct. DATE 10-16-84

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10-30-84

Subject to  
Like Approval  
by State