


Form 9-331a  
(Feb. 1961)



N. M. O. C. COPY  
(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 064790  
Unit F

RECEIVED  
JUL 1 1960  
D. C. O.  
ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

|  |                                     |  |  |
|--|-------------------------------------|--|--|
| NOTICE OF INTENTION TO DRILL                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF        |  |
| NOTICE OF INTENTION TO CHANGE PLANS            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     |                                     | SUBSEQUENT REPORT OF ALTERING CASING       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        |                                     | SUBSEQUENT REPORT OF ABANDONMENT           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    |                                     | SUPPLEMENTARY WELL HISTORY                 |  |
| NOTICE OF INTENTION TO ABANDON WELL            |                                     |  |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. Federal 18 is located 1980 ft. from N line and 660 ft. from W line of sec. 18  
SE/NE Sec. 18 (Range 19S Meridian 13E)  
Undesignated (County Las or Subdivision New Mexico)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to drill this well with rotary tools to an approximated depth of 3300 feet. Approximately 250 feet of 8 5/8" casing will be cemented back to the surface. Production string will be 5 1/2" casing set near bottom and cemented back to the anhydrite above the salt section. Pay interval will be cored. Well will be completed by perforating 5 1/2" casing.

RECEIVED

JUN 22 1960

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.

Company William A. and Edward R. Hudson

Address 1810 Electric Building

Fort Worth, Texas

By [Signature]

Title Edward R. Hudson  
Joint Operator