

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Dallas, Texas

September 2, 1943

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

PLACE

DATE

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

H. P. Taubman


Sun-State

Well No. 1 in NE 1/4 NE 1/4

COMPANY OR OPERATOR

LEASE

of Sec. 15, T. 17S, R. 34E, N. M. P. M., Vashon Field, Lea County.



The well is 660 feet (E.) (S.) of the North line and 660 feet (E.) (W.) of the East line of Section 15

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. 2-5090 Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is

Address

AREA 640 ACRES
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary from surface to approximately 1650' and after setting and cementing 8 5/8" OD casing, use cable tools to completion - estimated total depth 2000'

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: single well bond filed with Commission by National Surety Company

We propose to use the following strings of casing and to land or cement them as indicated:

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	NEW OR SECOND HAND	DEPTH	LANDED OR CEMENTED	SACKS CEMENT
15"	13" OD	48#	second hand	21'	Cemented	20 sacks
11"	8 5/8" OD	28# Galva	New	1650'	Cemented	300 "
8"	5 1/2" OD	144 J 55	New-seamless	4450'	Cemented	150 "

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4600 feet.

Additional information: The usage of cable tools below the point at which the 8 5/8" casing is cemented will afford thorough testing of formations encountered. The 8 5/8" OD casing will be cemented either by the two-stage method or 1" pipe will be run between the 1 1/2" and the 8 5/8" to approximately 200' and sufficient cement used to cement the 8 5/8" to the surface.

Approved _____, 19____

Except as follows: SEP 11 1943

"APPROVAL CONDITIONED UPON
COMPLIANCE WITH REQUIREMENTS
OF OPC-WPB."

Sincerely yours,

H. P. TAUBMAN

COMPANY OR OPERATOR

By

Position Operator

Send communications regarding well to

Name H. P. Taubman

Address 508 Gulf States Bldg. Dallas, Texas

OIL CONSERVATION COMMISSION,

By

Title

Roy Gunkrocy