

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate*
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM 02990

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Mescalero Ridge Unit

8. FARM OR LEASE NAME

9. WELL NO.
2

10. FIELD AND POOL, OR WILDCAT
Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
28-T19S-R34E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER Inject produced saltwater into well.

2. NAME OF OPERATOR
ATLANTIC RICHFIELD COMPANY

3. ADDRESS OF OPERATOR
P. O. Box 1920, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

660' FNL and 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3720' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
REPAIRING WELL
ALTERING CASING
ABANDONMENT*
(Other)

(Other) Convert to produced saltwater injection. (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth 13,710'. PFTD 3970'. Presently completed in perms. thru 9-5/8"OD casing @ 3860-3880'. Retainer @ 3970'. Cement plug in 9-5/8"OD casing @ 4969-4892'.

PROPOSE TO: Drill retainer @ PFTD 3970', drill cement and clean out to 4100'. Perforate 9-5/8"OD casing approx. 4020-4050' and acidize perms. w/approx. 1000 gals. NE acid. Run plastic coated 2-3/8"OD tubing and packer set @ approx. 3850' w/casing-tubing annulus filled w/treated water and utilize well to inject produced salt water into the Yates formation approx. 3860-4050'.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Superintendent

DATE

3-28-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Orig & cc: USGS, Hobbs

cc: Mrs. Marian M. Rhea, Supervisor Unit Division, State of New Mex. Box 1148, Santa Fe, New Mex.

cc: Partners, ~~see instructions on Reverse Side~~

cc: ~~file~~ Southern Region (West Texas)

cc: file