

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Roswell, New Mexico Feb. 10, 1950
Place Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____

Barnett & Rector State "F" Well No. 1 in SW1SW1
Company or Operator Lease
of Sec. 20, T. 17 S., R. 35 E., N. M. P. M., Vacuum Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

On Feb. 3, 1950, 7,100,000 cubic feet of gas per day was encountered at 3861-3863'. The gas tested: Nitrogen 75%, Methane 15%, Ethane 9%, Misc. 1%. Surface pressure was estimated at about 1050# to 1100#, making it impracticable to continue drilling. We propose to have Halliburton pump mud into the hole to kill the gas, and to cement 7" O.D. 20# J-55 new seamless casing at 3881' on Feb. 12, 1950, with 75 sacks of cement. After setting 72 hours, the cement plug will be drilled and the well tested for gas shut-off.

If a gas shut-off is obtained, we further propose to ~~not~~ drill to about 4350', and cement a liner of 5 1/2" O.D. 15# J-55 Seamless Casing from about 3725' to about 4350'. The liner will be cemented by Halliburton, with enough cement to circulate from the bottom to the top of the liner.

Approved _____, 19____
except as follows:

Barnett & Rector
Company or Operator
By John A. Barnett
Position Agent
Send Communications regarding well to
Name Barnett & Rector
Address Box 670,
Roswell, New Mexico.

OIL CONSERVATION COMMISSION,
By Roy Yunker
Title _____

1. The first part of the document is a list of names and addresses.

2. The second part of the document is a list of names and addresses.

3. The third part of the document is a list of names and addresses.

4. The fourth part of the document is a list of names and addresses.

5. The fifth part of the document is a list of names and addresses.

6. The sixth part of the document is a list of names and addresses.