

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
B-1722-1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
TEXACO Inc.

3. Address of Operator
P. O. Box 728, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER **L** **450** FEET FROM THE **West** LINE AND **1980** FEET FROM
THE **South** LINE, SECTION **30** TOWNSHIP **17-S** RANGE **35-E** N.M.P.M.
Vacuum Glorieta, Vac Abo N., Vac, Wolfcamp

7. Unit Agreement Name
-

8. Farm or Lease Name
N.M. 'N' State

9. Well No.
6

10. Field and Pool, or Wildcat
Vacuum Glorieta, Vac Abo N., Vac, Wolfcamp

15. Elevation (Show whether DF, RT, GR, etc.)
4003' (DF)

12. County
Ira


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Repair Water Flow <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Rigged up. Pull rods & pump in Glorieta String.
2. Set REP @ 4000' in Glorieta, Wolfcamp & Abo strings. Plugs tested OK. Spot 20' Sand on plugs.
3. Perforate 9 5/8" x 2 7/8" Csg W/2-shots @ 1600'.
4. Cement perfs @ 1600' W/700 Sx. Class 'H' cement containing 2% CaCl. Cement circulated. Squeeze W/add'l. 75 Sx. Class 'H' cement. WOC. DOC. Tested OK.
5. Install pumping equipment. Test & place on production, 8-13-81.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  TITLE **Asst. Dist. Mgr.** DATE **8-24-81**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: