

WELLBORE DIAGRAM

Basin Operating Company #1 Kimo Sabe State

1980 FSL & FEL
Section 16-T19S-R33E
Lea County, New Mexico
3648 GL

(Formerly King Resources #1 Kimo Sabe State, P & A 1973)

NOTES:

		Bit	Casing	Depth	Cement
	334'	17 1/2"	13 3/8"	334'	(surface) 275sx circ. Toc 550'
<p>2nd Stage DV tool at 2000' Pumped 730 sx BJ lite + 200 sx C</p>	550 TOC 2049'		9 5/8"		Stub at 2049'
<p>Delaware Wet Sandstones from 5969 to 7001</p>	5120' TOC 5263	12 1/4"	9 5/8"	Csg Shoe at 5120'	900 sx TOC at 5263'
<p>2 7/8 tubing to 7070' PACKER at 7030' Pay Zone 7177 - 7194 Brushy Canyon "I"</p>	5969 - 5977 6061 - 6067 6090 - 6096 6133 - 6139 6187 - 6203 6974 - 7001 7177 - 7194 7755'	(wet) (wet) (wet) (wet) (wet) (wet) (20% oil)			
<p>Note top 5 1/2 stub previously reported at 7400' but not found to 7755'. Top somewhere below 7755'.</p>		7 7/8"	5 1/2" 15.5 + 17#	7755'	1st stage Pumped 200 sx BJ lite, 300 sx C
	14	7 7/8"	5 1/2"	14446'	1000 sx

