

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331a for such proposals.)

- 1. Oil well Gas well Other
- 2. NAME OF OPERATOR
Harvey E. Yates Company
- 3. ADDRESS OF OPERATOR
P. O. Box 1933, Roswell, New Mexico 88201
- 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
- 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- 5. LEASE
NM - 036852
- 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
- 7. UNIT AGREEMENT NAME
Young Deep 3 Federal
- 8. FARM OR LEASE NAME
- 9. WELL NO.
#3
- 10. FIELD OR WILDCAT NAME
North Young Bone Spring
- 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T-18S, R-32E
- 12. COUNTY OR PARISH 13. STATE
Lea NM
- 14. API NO.
- 15. ELEVATIONS (SHOW DF, KDB, AND WD)
3887.1 GL

- REQUEST FOR APPROVAL TO: _____ SUBSEQUENT REPORT-GE. _____
- TEST WATER SHUT-OFF _____
- FRACTURE TREAT _____
- SHOOT OR ACIDIZE _____
- REPAIR WELL _____
- PULL OR ALTER CASING _____
- MULTIPLE COMPLETE _____
- CHANGE ZONES _____
- ABANDON* _____
- (other) Spud, 13 3/8" csg & 8 5/8" csg

NO. 15 Report results of multiple completion or zone change only. Form 9-335

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/6/81 Spudded @ 7:15 a. m.
 11/7/81 Operation WOC, Depth 658'.
 Ran: 17 jts 13 3/8" 54.5# ST&C MRJ 622.04
 Set @ 658'.
 Cement: 350 sx Pacesetter Lite "C" 2% Cacl 1/4# flocele.
 200 sx Class "C" 2% Cacl.
 PD @ 2230 11/6/81 w/600 psi. Held ok.
 11/8/81 Operation Repair BOP shaft, Depth 658'. Test BOP & csg w/500 psi - 30 min ok
 11/21/81 Operation WOC, Depth 3598'. RU, ran 8 5/8" csg 10 3/4 hrs. RU & ran 86 jts 24#, 28# & 32# 8 5/8" csg (3600') & set @ 3598'. Cmtd w/1300 sx Pacesetter Lite plus 2% CaCl, 1/4# Celloseal; followed by 200 sx Class "C" plus 2% CaCl. Plug down @ 1:30 a.m., 11/21/81 w/2000 psi. Plug did not hold. Circ. SWL record
 Subsurface Safety Valve Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct
 SIGNED Peck Hardee TITLE Peck Hardee DATE December 10, 1981
 DEC 15 1981

(This space for Federal or State office use)
 APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL IF ANY
 U.S. GEOLOGICAL SURVEY
 ROSWELL, NEW MEXICO