

DISTRICT I
 P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
 P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III
 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
 P.O. Box 2088
 Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33429
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease	B-155-1

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
 OIL WELL GAS WELL DRY OTHER _____

b. Type of Completion:
 NEW WELL WORKOVER DEEPEN PLUG BACK DIFF RES. OTHER _____

7. Lease Name or Unit Agreement Name
 VACUUM GLORIETA WEST UNIT

2. Name of Operator
 TEXACO EXPLORATION & PRODUCTION INC.

8. Well No. 89

3. Address of Operator
 205 E. Bender, HOBBS, NM 88240

9. Pool Name or Wildcat
 VACUUM GLORIETA

4. Well Location
 Unit Letter _____ : _____ 2000 Feet From The SOUTH Line and 1070 Feet From The EAST Line
 Section 36 Township 17-S Range 34-E NMPM LEA COUNTY

10. Date Spudded 6/5/96	11. Date T.D. Reached 6/13/96	12. Date Compl. (Ready to Prod.) 6/22/96	13. Elevations (DF & RKB, RT, GR, etc.) 3988' GR	14. Elev. Csghead 3988'
----------------------------	----------------------------------	---	---	----------------------------

15. Total Depth 6113' 6300	16. Plug Back T.D. 6300' 6256	17. If Mult. Compl. How Many Zones? -	18. Intervals Drilled By Rotary Tools 0-6300'	Cable Tools -
-------------------------------	----------------------------------	--	---	------------------

19. Producing Interval(s), of this completion - Top, Bottom, Name
 5944'-6068' (VACUUM GLORIETA)

20. Was Directional Survey Made
 YES

21. Type Electric and Other Logs Run
 CNL/DLL/MCFL/GR

22. Was Well Cored
 NO

23. CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8 5/8"	24#	1540'	11"	CL-C 550 SX, CIR 113	
5 1/2"	15.5 & 17#	6300'	7 7/8"	C&H 1325 SX, CIR 139	

24. LINER RECORD **25. TUBING RECORD**

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	6080'	

26. Perforation record (interval, size, and number)
 5944'-5978', 6000'-6016', 6028'-6044', 6054'-6068' (2 JSPF, .40", 84 NET FEET, 168 HOLES)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5944'-6068'	SPOT 200 GALS ACETIC ACID
5944'-6068'	ACID - 8,000 GALS 15% NEFE HCL

28. PRODUCTION


Date First Production 6/22/96	Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING (2 1/2" X 2" X 24')	Well Status (Prod. or Shut-in) PROD.					
Date of Test 6/24/96	Hours tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 456	Gas - MCF 144	Water - Bbl. 94	Gas - Oil Ratio 316
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.) 38.6	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
 SOLD

Test Witnessed By
 LOCKLAR

30. List Attachment DEVIATION SURVEY

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Engr Asst DATE 7/3/96

TYPE OR PRINT NAME Monte C. Duncan Telephone No. 397-0418

JL

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta 5830'	T. McKee
T. Paddock 5932'	T. Ellenburger
T. Blinberry	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo	T.
T. Wolfcamp	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 5700' to 6200'	No. 3, from _____ to _____
No. 2, from _____ to _____	No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from _____ to _____ feet	
No. 2, from _____ to _____ feet	
No. 3, from _____ to _____ feet	

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
5800'	5830'	30	LIMESTONE				
5830'	5942'	112'	DOLOMITE				
5942'	6050'	108'	LIMESTONE				
6050'	6283'	233'	DOLOMITE				