

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
MAR 3 1948
RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

February 29, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation J. R. Phillips Well No. 6 in the _____

Company or Operator

Lease

NW 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,

Monument-Paddock Field, Lea County.

The dates of this work were as follows: February 28, 29, 1948

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on February 28, 1948

and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5207' Total Depth, Line; 5126' bottom of 8-3/4" hole. Ran Schlumberger Survey. Ran a total of 121 joints of 7" CD, 23#, J-55 & N-80, R-2&3, 8-RT, SS Casing New with the top 5 joints being N-80 and set at 5126' with 10 Larkin Centralizers set at 5111', 5081', 5051', 4000', 3970', 3940', 3910', 3880', 3850' and 3820'. Cemented with 600 sx. of Trinity Cement mixed 2% Howoogel and 200 sx. of Trinity Regular Cement and plug pumped to 4983' at 5:15PM, 2-29-48. Final pressure 2100#. Lost circulation last 150' of pumping and when pressure built up to 2100# stopped pumping.

Witnessed by D. F. Furse Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

29th. day of February, 19 48

Name Don Furse

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____ My Commission Expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED MAR 14 1948

Date _____

Roy Yarbrough
Name
OIL & GAS INSPECTOR