

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
B154

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "D"
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE. SECTION <u>1</u> TOWNSHIP <u>20S</u> RANGE <u>36E</u> N.M.P.M.	10. Field and Pool, or Wildcat Eunice/Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3608' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK  PLUG AND ABANDON   
TEMPORARILY ABANDON  CHANGE PLANS   
PULL OR ALTER CASING  OTHER

SUBSEQUENT REPORT OF:

REMEDIAL WORK  ALTERING CASING   
COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
CASING TEST AND CEMENT JOBS  OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

August 20, 1984 to August 31, 1984 - Pulled rods, pump & tbr. Spotted 7 sks. Class C neat cement in open hole fr. 3880' to 3860'. Ran pkr. & tbr., set pkr. at 3701'. Acidized G/SA zone in open hole fr. 3760' to 3860' w/1000 gal. 15% NE - FE acid in two stages using rock salt as diverter. Swabbed. Set retrievable bridge plug in 7" csa. at 3754'. Set pkr. at 3739' & tested bridge plug w/2000#. Held OK. Spotted 250 gal. 7-1/2% acetic acid in 7" csa. at 3750'. Perf. 7" csa. opposite G/SA zone selectively fr. 3688' to 3744'. Set pkr. at 3640' & acidized G/SA zone thru 7" csa. perf. fr. 3688' to 3744' w/2000 gal. 15% NE - FE acid using ball sealers as diverter. Swabbed. Chanced out tbr. head. Re-ran tbr., pump & rods. Chanced out 228 pump unit for 456 pump unit and resumed production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Adm. Ser. DATE 8-31-84

ORIGINAL SIGNED BY JERRY SEKTON

APPROVED BY A. DISTRICT 1 SUPERVISOR TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: