

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**DISTRICT I**  
P.O. Box 1980, Hobbs NM 88241-1980

**DISTRICT II**  
P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-04165

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.  
A-1375-39

7. Lease Name or Unit Agreement Name  
North Monument G/SA Unit Blk. 18

8. Well No.  
1

9. Pool name or Wildcat  
Eunice Monument G/SA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL  GAS WELL  OTHER Water Injection Well

2. Name of Operator  
Amerada Hess Corporation

3. Address of Operator  
P. O. Box 840, Seminole, Texas 79360

4. Well Location  
Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line  
Section 2 Township 20S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3590' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to MIRU pulling unit. Remove wellhead, install BOP & TOH w/tbg. & pkr. Spot 145 sks. sand in open hole & csg. to 3761'. TIH w/cement retainer set at +/- 3725'. Cement squeeze perms. fr. 3720' - 3761' w/200 sks. Class "C" cement w/latex additive. Drill out cement to 3750' & press. test csg. to 500 PSI. Drill out remaining cement & clean out sand to TD at 3945'. TIH w/pkr. & continue inj. water.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Bus. Svc. Spec. II DATE 4-28-2000

TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915 758-6700

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: