

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

RECEIVED
DEC 10 1940
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Set liner etc.	XX

Hobbs, New Mexico. Dec 9, 1940

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corp - GYPROD B. Whitmire Well No. #2 in the

Company or Operator Lease
C NW4 of NE/4 of Sec. 8, T. 20S, R. 37E, N. M. P. M.,
Monument Lea County

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19____ and approval of the proposed plan was (was not) obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Oct 9, 1940 ran 4 joints of 5 1/2" OD 6.8# Securaloy Liner with Hydrill flush joint thread set on bottom (Tally including adapter 21' 11) top of liner at 3809' 1". Cemented with 15 sack cement with 10# Dowell J-4 mixed with first 10 sacks (Perforated liner by Lane Wells from 3864' to 3871' 6" incl., with 35 shots at 4" intervals) Also (Lane wells perforated liner with 12 holes at 6" intervals from 3849' 6" to 3844' incl, ran 2" EUE x 4 1/4" x 48" rubber Lane Wells Anchor formation packer set at 3864' with 5' of perforations 10' above packer, tubing set on bottom) November 27, 1940 acidized with 500 gallons Dowell IX, flushed with 15 barrels oil.

Production before:- On may 5, 1940 tested 99 barrels oil & 20 brls water in 24 hours thru 2" tubing wide open gas 1,117,929 cu ft GOR 11,292.

Witnessed by Prod after:- Flowed 43 barrels oil and 1 1/2 brls water in 24 hours thru 1/2" & 3/4" chokes wide open casing pres. 300#, tubing 150# Gas 257,700 cu ft. GOR 5,125.

Subscribed and sworn to before me this _____

I hereby swear or affirm that the information given above is true and correct.

9th day of December, 19 40

Name *[Signature]*

[Signature]
Notary Public

Position District Supt.

Representing Gulf Oil Corp - Gypsy Prod Diva.

My Commission expires February 25, 1942

Address Hobbs, New Mexico.

Remarks:

[Signature]
Name
OIL & GAS INSPECTOR
Title

