

NEW MEXICO OIL CONSERVATION COMMISSION

COPIES RECEIVED		
DISTRIBUTION		
SALARY		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
B-869

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "F"
3. Address of Operator Drawer "D", Monument, New Mexico 88265	9. Well No. 4
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE west LINE, SECTION 36 TOWNSHIP 19-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Eunice-Monument (G-S)
15. Elevation (Show whether DF, RT, GR, etc.) 3595' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled production equipment. Set Hall. cast iron bridge plug at 3720' w/10' cement on top. Perforated 6-5/8" csg. from 3484' to 3489', 3500' to 3506', 3526' to 3534', w/ 3 shots per foot. Acidized perfs. 3484' to 3534' w/3000 gals. 15% N E Acid. Swab tested. Perforated 6-5/8" csg. 3506' to 3512', 3515' to 3520', 3540' to 3550', 3554' to 3561' w/one (1) shot per foot. Acidized Perfs. 3483' to 3561' w/ 4500 gals. 15% N E Acid w/ ball sealers. Swab tested.

Non Commercial

Closed All Valves & Temp. Abandoned

TA Expires 9/15/76

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE SUPVR. ADM. SERV. DATE SEP 12 1975

APPROVED BY [Signature] TITLE Geologist DATE SEP 16 1975

CONDITIONS OF APPROVAL, IF ANY: