

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-100
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

14. Indicate Type of Lease
State Fee

15. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
Amoco Production Company

3. Address of Operator
P. O. Box 68, Hobbs, New Mexico 88240

4. Location of Well
SL/BHL UNIT LETTER N 577/1310 FEET FROM THE South LINE AND 1984/2475 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 19-S RANGE 38-E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
South Hobbs (GSA) Unit

9. Well No.
145

10. Field and Pool, or Wildcat
Hobbs GSA

15. Elevation (Show whether DF, RT, GR, etc.)
3605.9' GL

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a total depth of 4498'. On 10-19-83, ran 5-1/2" 15.5# K-55 casing and set at 4498' with DV tool at 3392'. Cemented first stage with 250 sx class H and additives. Opened DV tool and circulated out 23 sx of cement. Cemented second stage with 750 sx class H with additives and tailed-in with 400 sx class H and additives. Circulated out 373 sx of cement. Rig released 1:30 p m, 10-19-83. Drill out and pressure test will be performed by completion unit.

0+4-NMOCD,H 0+4-NMOCD,H 1-HOU R. E. Ogden RM 21.150 1-F. J. Nash, HOU RM 4.206 1-CMH
1-Texaco 1-Shell 1-Sun 1-Petro Lewis

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herring TITLE Administrative Analyst DATE 10-20-83
ORIGINAL SIGNED BY EDDIE SEAY
APPROVED BY OIL & GAS INSPECTOR DATE OCT 26 1983

CONDITIONS OF APPROVAL, IF ANY: