

















		O.D.	I.D.	LENGTH	DEPTH	
1		DRILL PIPE.....	3.500	2.602	13393.0	
3		DRILL COLLARS.....	4.750	2.375	887.0	
50		IMPACT REVERSING SUB.....	4.750	2.250	1.0	14281.0
3		DRILL COLLARS.....	4.750	2.375	124.0	
5		CROSSOVER.....	4.750	2.250	1.0	
5		CROSSOVER.....	4.750	2.125	1.0	
62		MULTIPLE CIP SAMPLER.....	3.875	0.620	11.0	14412.0
14		EXTENSION JOINT.....	3.875	0.620	5.0	
14		EXTENSION JOINT.....	3.875	0.620	5.0	
14		EXTENSION JOINT.....	3.875	0.620	5.0	
80		AP RUNNING CASE.....	3.875	3.000	6.0	14437.0
15		JAR.....	3.875	1.250	7.0	
18		VR SAFETY JOINT.....	3.875	0.750	4.0	
71		CASING PACKER.....	5.650	2.000	6.0	14453.0
20		FLUSH JOINT ANCHOR.....	3.750	3.000	10.0	
81		BLANKED-OFF RUNNING CASE.....	3.750		5.0	14469.0
TOTAL DEPTH						14689.0

RECEIVED

JAN 25 1985

O.C.D.
HOBBES OFFICE