

BLM - ~~Carlsbad~~
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR: CONOR INC

3. ADDRESS OF OPERATOR: P.O. Box 460, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface: UNIT K

14. PERMIT NO.: 1980' J5W & 1980' FwW, Sec. 25, T20S, R. 37E
30-025-06259

15. ELEVATIONS (SHOW WHETHER DF, RT, GR, etc.)

5. LEASE DESIGNATION AND SERIAL NO.: LC-031696A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME: SEMIL Eumont

9. WELL NO.: 54

10. FIELD AND POOL, OR WILDCAT: Eumont Gates 7 RURS Queen

11. SEC., T., R., M. OR BLM. AND SURVEY OR AREA: Sec. 25, T20S, R. 37E

12. COUNTY OR PARISH: Lea

13. STATE: NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other):

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other):

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- dk (1) Milk Ru. PootH w/ rods & tbg. Swirlge out 25cy to 750'. Set CIBP @ 3704'. Circ. w/ 10 ppg mud & spot 25.5x class C
- dk (2) PootH w/ tbg to 1300' & spot 60.5x class C next from 1300' - 720'. Pmp 300 sf class C w/ 2" incl down 5 1/2" iscy. Pump any remaining
- (2a) Cement down 8 5/8" - 5 1/2" annulus.
- dk (3) Hole in casing at 600' - will circulate 5 1/2" & 8 5/8" annulus to surface and leave plug in 5 1/2" from 600' to surface.
- dk (3) Cut off 25cy 3' below ground level & install P4A marker. Ring down.
- dk (4) A proposed P4A sketch is attached.

18. I hereby certify that the foregoing is true and correct

SIGNED: [Signature]

TITLE: Administrative Supervisor

DATE: 2-9-87

(This space for Federal or State office use)

APPROVED BY: [Signature]

TITLE: _____

DATE: 2-25-87

CONDITIONS OF APPROVAL, IF ANY:

*See instructions on Reverse Side