

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PERORATION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed; and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

October 29, 1964  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Texas Pacific Oil

Company's S. E. Cone Well No. 1 in J  
(Company or Operator) Lease (Unit)  
NW 1/4 SE 1/4 of Sec. 26, T. 21-S, R. 7, NMPM, Tubb Gas Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Squeeze Blinebry Gas horizon 5550-5675 with 200 sks.
2. Drill out cement and bridge plug at 6348 to 6590' TD.
3. Run frac tubing and treat open hole 6450-6590 w/30,000 gals. crude oil & 30,000# sand. Treat perforated interval 6400-6424' w/25,000 gal. crude oil, 37,500# sand & 1250# Adomite.
4. Perforate Blinebry at 5693, 5703, 5713, 5723, 5729, 5740, 5751, 5760, 5783, 5801, 5808, 5821, 5830, 5837, 5847, 5850 and 5858.
5. Run frac tubing w/straddle packers and set at 5680-5770'. Frac in two equal stages; 25,000 gals per stage, 37,500# sand per stage & 1250# Adomite per stage.
6. Set production packer at 5675' and run "Triple String Flow Tube" on long string.
7. Run Blinebry string and triple complete.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:

TEXAS PACIFIC OIL COMPANY  
By John H. [Signature]  
Position District Engineer  
Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By \_\_\_\_\_  
Title \_\_\_\_\_

Name Texas Pacific Oil Company  
Address P.O. Box 1069, Hobbs, New Mexico