

DUPLICATE
RECEIVED
JUL 12 1951
SUNDENSAATION COMMISSION
HOBBS OFFICE

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces
Lease No. 031670 (a)
Unit N.M.P.U.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

SEMI-Burger A-19 NO. 8

Hobbs, New Mexico July 9, 19 51

Well No. 8 is located 660 ft. from N line and 1980 ft. from W line of sec. 19

W/4 Sec. 19
(1/4 Sec. and Sec. No.)

20S
(Twp.)

36E
(Range)

N.M.P.M.
(Meridian)

Slaggs
(Field)

Lea
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well at above location to a depth of approximately 3700' with rotary tools, and to drill thru pay zone to a total depth of approximately 3920' with reverse circulation rig. If necessary, the pay will be shot with SNG and the hole cleaned out to total depth. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing patterns: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated to surface; 7" casing to be set at approximately 3700' and cemented with approximately 1570 sacks, or sufficient cement to protect the salt section.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title District Superintendent

