

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.6.

5. LEASE DESIGNATION AND SERIAL NO.

LC-031736 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

GILLULY "B" Federal

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

WEIR DRINKARD OIL

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

22-20-37 NMPM

12. COUNTY OR PARISH
LEA

13. STATE
N.M.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL GAS WELL DRY Other _____

b. TYPE OF COMPLETION:

NEW WELL WORK OVER DEEP-EN PLUG BACK DIFF. RESVR. Other _____

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR
BOX 68, MOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface
2085' FNL x 1874' FEL Sec. 22 (Unit G, SW/4 NE/4)

At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 16. DATE T.D. REACHED 17. DATE COMPL. (Ready to prod.) 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 19. ELEV. CASINGHEAD

8-12-68 8-31-68 9-14-68 3451' R.D.B. -

20. TOTAL DEPTH, MD & TVD 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 25. WAS DIRECTIONAL SURVEY MADE

7805' 7310' -> O-TD -

6781-89, 6809-16, 24, 33-38 LOWER DRINKARD No

26. TYPE ELECTRIC AND OTHER LOGS RUN 27. WAS WELL CORED

Some GR, Dual Ind Petrology No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48 [#]	324'	17 1/2"	350 Sx	
9 5/8"	32.3 - 36 [#]	3777'	12 1/4"	1350 Sx	
5 1/2"	14 - 15.5 [#]	7805'	8 3/4"	1050 Sx	

29. LINER RECORD 30. TUBING RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	6830'	

31. PERFORATION RECORD (Interval, size and number) 32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

PERFORATION RECORD	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
7792-96' w/2JSPF - SQZ. w/ 35 Sx.	DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED
7360-62, 64-66, 69-72, 91-93, 7400-02, 11-14' w/2JSPF - SQZ. w/ 50 Sx.	7792-96' 500 gal acid 15%
6781-89, 6809-16, 24, 33-38 w/2JSPF	7360-7414' 1500 " " "
	6781-6838' 3000 " " "

33. PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)					
9-16-68	FLW - TO BE PUT ON PUMP.	PRODUCING					
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
9-17-68	24	48/64"	->	70	NA	236	NA
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
25-100	-	->					

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) TEST WITNESSED BY

Vent

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED _____ TITLE AREA SUPERINTENDENT DATE 9-18-68

048- USGS-H
1- NSW
1- W 7
2.2.1

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 33.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURE, AND RECOVERIES		38. GEOLOGIC MARKERS					
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP	TRUE VERT. DEPTH
<i>Sandstone</i>	6781'	6814'	<i>Oil & Gas Prod Zone.</i>	YATES	2558		
<i>Clay</i>	7360	7414	<i>Dry</i>	SAN ANDRES	3941		
<i>Sand</i>	7792	96	<i>Dry</i>	GLORIETA	5224		
				BLINESEY	5785		
				TUBB	6300		
				DRINKARD	6390		
				ABO	6980		
				STRAWN	7720		