

ITEM	DESCRIPTION	A. B. QUANTITY	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/sq. nut, round washer, and corner key on short end, sq. nut and WP locknut on long end, 15 1/8" long (for length required.) wet process porcelain secondary spool insulator, 3", brown glaze	7#28			
b	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-18 Note: provide clamp and ground conduit parallel bronze clamp, size req'd		1/0/01		
d	secondary insulator clevis for 4" insulator	65/0		BURNBY STRIPS UC	
f	5/8" thimble nut	55/2			
g	5/8" x 12" (for length req'd) straight thimble bolt w/sq. nut			ALUMINUM 6M3-6	X
j	transformer cluster mount bracket (small)			ALUMINUM 6M3-6	X
l	transformer cluster mount bracket (large)				X
m	req'd size ralnlight disconnect & fuses, 3-phase, 600 V. Ref. Dwg. No. ES-10.	X-16			
n	16" stone plate anchor (for size req'd)	88/35			
q	8-way expanding anchor (size req'd)		10/01		
t	4" brown glaze wet process porcelain secondary spool insulator				
u	5/8" x 7" thimble anchor rod w/nut (use twineye if req'd - Chance No. 5367)	53/7 (nut 550066)			
aa	3/8" high strength guy strand (10,800 lb.)				
ab	preformed guy grip for 3/8" guy strand	50/0			
ad	5/8" x 10" angle thimble bolt w/nut	68/23 1/2			X
ae	3" x 1/2" x 11/16" hole curved washer				
ef	6" - guy clamp w/3-1/2" bolts	6454			
eg	medium size strain insulator	7887			X
eh	receiving sleeve for 3/8" guy strand				
hj	3/16" x 2-1/2" x 7" lite plate				
mm	pole bottom ground plate (may use butt-wrap if desired)				
ng	Ground connection (See Dwg. ES-12)				
nt	wet process porcelain secondary spool insulator, 3" - white glaze				
tc	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71	TITLE: DESCRIPTION MATERIALS
DRAWN BY: E. WINTER	
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	
	CONOCO
	HOBBBS DIVISION
JOB: ELEC SPEC'S	DRAWING NO: ES-1
	SHEET 5 OF 7