



NOTES:
 1. ALL JUMPERS OR CONDUCTOR SPICES WILL BE INSULATED TYPE WIRE.
 2. THIS CONSTRUCTION STANDARD TO BE USED ON ALL LINES BUILT ON NATIONAL RESERVE LANDS.
 3. DO NOT INSTALL GROUND WIRE PART NEUTRAL CONDUCTOR.

WIRE LEADS WILL BE 1/4" ON ANGLES OF 60°-90° AND 1/2" ON ANGLES OF 60°-74°

ITEM	DESCRIPTION	QUANTITY
1	POLE	1
2	ANCHOR ROD, 3/4" x 7'	2
3	WIRE ATTACHMENT PLATE	2
4	WIRE CABLE, 3/8" U/L	24
5	WIRE INSULATOR, 2X3	2
6	FRONT INSULATOR, 2X3	2
7	CLAMP, 3/8" DIA	2
8	WIRE GRIP, 3/8" DIA	2
9	WIRE ARM, 8"	4
10	POLE, 2X3 SPM	4
11	STEEL PIN, 3/8" x 5"	2
12	WIRE, 3/8" U/L	2
13	WIRE, 3/8" U/L	2
14	WIRE, 3/8" U/L	2
15	WIRE, 3/8" U/L	2
16	WIRE, 3/8" U/L	2
17	WIRE, 3/8" U/L	2
18	WIRE, 3/8" U/L	2
19	WIRE, 3/8" U/L	2
20	WIRE, 3/8" U/L	2
21	WIRE, 3/8" U/L	2
22	WIRE, 3/8" U/L	2
23	WIRE, 3/8" U/L	2
24	WIRE, 3/8" U/L	2
25	WIRE, 3/8" U/L	2
26	WIRE, 3/8" U/L	2
27	WIRE, 3/8" U/L	2
28	WIRE, 3/8" U/L	2
29	WIRE, 3/8" U/L	2
30	WIRE, 3/8" U/L	2
31	WIRE, 3/8" U/L	2
32	WIRE, 3/8" U/L	2
33	WIRE, 3/8" U/L	2
34	WIRE, 3/8" U/L	2

DATE: 7-15-77	TITLE: PRIMARY ANGLE STRUCTURE
DRAWN BY: T. W. P. III	60°-90° 125KV VOLT ASGR
DESIGN BY:	
CHECKED BY: SP	CONOCO
APPROVED BY: SP	PRODUCTION DEPT.
SCALE: 1/16" = 1'	JOB: ELIC. SPURS.
	HOBBS DIVISION
	DRAWING NO: ES-21