

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No.

NM 64605

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Rosemary AJB Federal *1*

9. API Well No.

30-025-31227

10. Field and Pool, or Exploratory Area

west
~~Und. Livingston Ridge Delaware~~

11. County or Parish, State

Lea County, NM

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980' FSL & 660' FWL, Sec. 6-22S-32E *L*

12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent
 Subsequent Report
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other Spud, set surface casing
 Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut-Off
 Conversion to Injection
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 5:00 PM 4-26-91 with Auger Air. Ran 40' of 20" conductor. Cemented with 2 1/2 yards redimix to surface.
4-28-91. Ran 20 joints 13-3/8" J-55 54.5# casing set 862', Guide shoe set 862', insert float set 819'. Cemented w/400 sx Pacesetter Lite 65/35/6 with 2% CaCl2 (yield 1.76, wt. 12.8). Tailed in w/200 sx "C" neat with 2% CaCl2 (yield 1.33, wt 14.8). PD 12:05 AM 4-29-91. Bumped plug to 550 psi, released pressure and float held okay. Circulated 122 sacks to pit. WOC. Drilled out 12:15 AM 4-30-91. WOC 24 hrs and 10 mins. NU and tested to 1000 psi for 45 minutes. OK. Reduced hole to 11". Note: Witnessed by BLM, Hobbs, NM.

ACCEPTED FOR RECORD

MAY 1 1991

CARBON NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed *Gasparita Rosillo*

Title Production Supervisor

Date 5-6-91

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date