

COPIES RECEIVED		
DISTRIBUTION		
DATE		
BY		
OFFICE		
OPERATION		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fed
5. State Oil & Gas Lease No.
E-8241

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSED TO RE-OPEN OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO RE-OPEN OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR")

1. OIL WELL GAS WELL OTHER

2. Name of Operator
THE SUPERIOR OIL COMPANY

3. Address of Operator
P.O. BOX 71 CONROE, TEXAS 77301

4. Location of Well
UNIT LETTER G 1575 FEET FROM THE North LINE AND 1650 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 21S RANGE 35E NMPM.

7. Unit Agreement Name

8. Form or Lease Name
STATE "334"

9. Well No.
4

10. Field and Pool, or Wildcat
Eumont (Oil)

11. Elevation (Show whether DF, KT, GR, etc.)
GR: 3597

12. County
LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING
 TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
 PULL OR ALTER CASING OTHER CASING TEST AND CEMENT JOB
 OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was temporarily abandoned 6-1-59 after attempting recompletion in the present Yates sand perforations at 3823'-3832'. Present PBDT is 3851'. Top of cement outside 7" casing is 2605'. Surface pipe is set to 315'. Plugging procedure will be:

1. Displace fluid in hole to mud laden fluid.
2. Equalize a 35 sack cement plug across the perforations to extend from 3670' to PBDT.
3. Recover as much 7" casing as practical (estimated 2000').
4. Place a 50 sack cement plug from about 50' below the base of the surface casing to 80' above the casing shoe (365'-235').
5. Cut off 9-5/8" casing at the surface if necessary and place a 5 sack cement plug in top of casing.
6. Weld a steel plate on top of 9-5/8" casing and install a steel marker at least 4" in diameter extending at least 4' above ground level.
7. Mark the steel marker showing the following information:
State 334 #4 G Sec. 3-21S-35E

** E. Jones 11/1/76*

xc: OCC (3), WNM, JVL, FILE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: P. R. Blumert TITLE: OPERATIONS ENGINEER DATE: JULY 2, 1976

APPROVED BY: John Runyan TITLE: Geologist DATE: 7/2

CONDITIONS OF APPROVAL, IF ANY: 142 ± 1600' if not behind pipe

Vertical line on the left side of the page.

Small mark or dot.

Vertical line on the right side of the page.