

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	X
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

October 24, 1960
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Albert Gackle, Operator **Sinclair State "A"** Well No. **2** in **K**
(Company or Operator) ^{Lessee} (Unit)
NE $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **23**, T. **23 S**, R. **36 E**, NMPM, **Jalmat** Pool
(40-acre Subdivision) **Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Permission is hereby requested to deepen this well from its present T.D. of 3,300' to approximately 3,725'. This well was originally completed on Sept. 12, 1949, as a gas well in the Jalmat Gas Pool at a T.D. of 3,300'. 5 1/2", 14#, J-55 casing was set @ 2,795' and cemented with 500 sacks. The well potentialled for 14,000 MCF/GPD. The well was temporarily abandoned and acreage dedicated to well No. 1. We now propose to core this well from 3,300' to 3,725' with 4 3/4 corehead and then underream to at least 6 inches and run a 4 1/2", 9 1/2#, J-55 liner to T.D. and cement with a sufficient number of sacks to tie the two strings together & pressure test with a minimum of 600# to test pipe.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION
By: *[Signature]*
Title

ALBERT GACKLE, OPERATOR
Company or Operator
By: *[Signature]*
R. F. Montgomery
Agent
Position.....
Send Communications regarding well to:

Name..... **Albert Gackle, Operator**
Address..... **P. O. Box 2076**

Hobbs, New Mexico