

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL FORM C-101 FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. <b>L-4523</b>
6. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
8. Operator Name <b>Amoco Production Company</b>		8. Form or Lease Name <b>State IK</b>
9. Address <b>P. O. Box 68, Hobbs, NM 88240</b>		9. Well No. <b>1</b>
10. Unit Location UNIT LETTER <b>C</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM <b>West</b> LINE, SECTION <b>10</b> TOWNSHIP <b>23-S</b> RANGE <b>33-E</b> NMPM.		10. Field and Pool, or Wildcat <b>Wildcat Bone Springs</b>
11. Elevation (Show whether DF, RT, GR, etc.) <b>3590.6' GL</b>		11. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Plug back</u> <input checked="" type="checkbox"/>

12. Description of Nature of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set a cast iron bridge plug at 11950' and capped with 35' cement. Perforated 11704-11710', 11712-11718', and 11720-11725' with 2 JSPF. Swabbed tested and recovered 42 BBLS water and slight show of gas after each run. Acidized with 3000 gal 15% HCl acid and additives. Currently swab testing.

0+4-NMOCD,H 1-Hou 1-Susp 1-LBG 1-W.Stafford, Hou 1-Superior, Con 1-Superior, Mid  
1-EI Paso 1-Beard 1-Southland 1-L&M Walter 1-Supron 1-Crown 1-Central

I, Thereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Asst. Admin. Analyst DATE 1-8-81

Jerry Sexton  
Dist. 1. 2. 3.

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

JAN 13 1981

CONDITIONS OF APPROVAL, IF ANY: