Form C-103

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

DUPLICATE

RECEIVED JUL 2 1946 HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico (Place) May 20, 1946 (Date)

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Anderson-Prichard Oil Corporation (Company or Operator) State "A" #28 (Lease) Well No. 2 in the C SW 1/4 of NE 1/4 of Sec. 28, T. 26S, R. 37E, N. M. P. M., Rhodes Field, Lea County.

The dates of this work were as follows:

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on 8-21 1943

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Bridged 5-1/2" casing from 2750 to 2809 with brick and pea gravel. Spotted cement plug from 2706 to 2750. Ran tubing and circulated hole above 2706 full of 10-1/2# mud. Shot and pulled 5-1/2" OD casing from 2169. Ran tubing and spotted cement plug from 1143 to 1273. Pulled tubing and spotted 10' plug of cement in 8-5/8" surface casing which was left in hole. 4" regulation pipe marker was cemented in surface casing.

Witnessed by _____ (Name) _____ (Company) _____ (Title)

Subscribed and sworn before me this 20th day of May, 1946

Notary Public

My commission expires 3/18/50

I hereby swear or affirm that the information given above is true and correct.

Name [signature]

Position District Clerk

Representing Anderson-Prichard Oil Corporation (Company or Operator)

Address Box 1697, Hobbs, New Mexico

Remarks: APPROVED

Date JUL 25 1946

[signature] (Name)

Oil & Gas Inspector (Title)