

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L.C-030174-(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
TEXACO INC.

8. FARM OR LEASE NAME

W.H. RHODES "B" FED NCT-2

3. ADDRESS OF OPERATOR
P. O. BOX 728, HOBBS, NEW MEXICO 88240

9. WELL NO.

5

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT

RHODES-YATES

1980' FSL, 1980' FEL OF SECTION 28, T-26-S,
R-37-E, UNIT LETTER "J", LEA COUNTY, NEW
MEXICO

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 28, T-26-S, R-37-E

14. PERMIT NO.

REGULAR

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2966' (GR)

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH 3450'
PLUG BACK TOTAL DEPTH 3320'
8-5/8" OD 24# K-55 CSG SET @ 650'
5-1/2" OD 14# K-55 CSG SET @ 3450'

- PERFORATE 5 1/2" OD CSG W/2-JSPF @ 3353', 58', 64' & 3370'.
- SET PKR @ 3260'. ACIDIZE 5 1/2" CSG PERFORATIONS 3353'-3370' W/1000 GAL. 15% MUD ACID W/16 BALL SEALERS.
- SET CIBP @ 3330' & DUMP 1 SX CEMENT ON PLUG. PBTD 3320.
- PERFORATE 5 1/2" OD CSG W/2-JSPF @ 3280', 84', 92', 98', & 3302'.
- SET PKR. @ 3191'. ACIDIZE PERFORATIONS 3280'-3302' W/850 GAL 15% MUD ACID USING 24 BALL SEALERS. FLUSH W/16 BBL. 2% KCL WTR.
- FRAC PERFORATIONS 3280'-3302' W/18000 GAL GELLED WATER & 8900 GAL CO2 CARRYING 10,000# 100-MESH SAND & 41,000# 20-40 SAND. FLUSH W/52 BBL. KCL WATER.
- INSTALL PUMPING EQUIPMENT. ON 24 HR. POTENTIAL TEST ENDING 2/24/78 WELL PUMPED 4 BO, 14 BW, GOR 820.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE ASST. DISTRICT SUPT.

DATE 2/27/78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE
ACCEPTED FOR RECORD
MAR 2 1978

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO