

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION
O+2-NMOCC-HOBBS 9-WIO'S
1-R.J. STARRAK-TULSA 1-A.B. CARY-MIDLAND
1-E.L. BUTTROSS-ENGR. 1-H.C. LITTLE-FOREMAN
1-FILE 1-BH

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.
B-1327

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO ABANDON OR TO OPEN OR REOPEN A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO ABANDON OR TO OPEN OR REOPEN A DIFFERENT RESERVOIR.

1. OIL WELL GAS WELL OTHER

7. Unit Agreement Name
MYERS LANGLIE
MATTIX UNIT

2. Name of Operator
GETTY OIL COMPANY

6. Farm or Lease Name

3. Address of Operator
P. O. BOX 730, HOBBS, NEW MEXICO 88240

9. Well No.
92

4. Location of Well
UNIT LETTER J 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM
EAST LINE, SECTION 32 TOWNSHIP 23-S RANGE 37-E N.M.P.M.

10. Field and Pool, or Wildcat
LANGLIE MATTIX

15. Elevation (Show whether DF, RT, CR, etc.)
3294' G.L.

12. County
LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 3756'. On 6-28-78 set 5-1/2" 15.5# 8R K-55 at 3756'. Halliburton cemented with 750 sxs. Lite Wate, 15# Salt, 1/4# Flo-Cele, 2% CaCl, and 200 sxs. Class "C" Cement with 2% CaCl and 1/4# Flo-Cele/Sk. Cement Circulated. WCC 24 hrs. Tested 5-1/2" Casing with 1200# for 30 Minutes. O:K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: [Signature] TITLE: AREA SUPERINTENDENT DATE: 7-20-78

APPROVED BY: [Signature] TITLE: Dist. 1, Supv. DATE: JUL 24 1978

CONDITIONS OF APPROVAL, IF ANY: