

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER REF. NO.	NO. SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2X10/56			X
AB	General Purpose 10" bolt clamp	UC310AGP			
AC	Lightening arrester, 10 KV				
AD	Single phase oil switch, 16.4 KV				
AE	Split bolt connector, size req'd				
AF	Grounding spec. see det No. ES-11 & ES-1A, Note 3				
AG	35' class 4 creosoted pine pole				
AH	Aluminum deadend preforms for ASR, size req'd				
AI	30' class 6 creosoted pine pole				
AJ	OVERHEAD GRND, #4 ACSR - 11' Req'd - Ref. Det ES-11,				
AK	ES-1A - Note 3				
AL	Ground connector, motor				
AM	600 V. secondary lightning arrester simple phase				
AN	Greenfield Type RF liquid-tight flexible steel conduct, size req'd, w/ necessary liquid-tight connectors.				
AO	req'd size LB fitting & cover & panel				
AP	transformer tank grounding terminal	GWS-15			
AQ	Bird Guards (insulating boots on transformer bushings)				

DATE:	12-27-71	TITLE:	DESCRIPTION MATERIAL
DRAWN BY:	E. WINTER	CONOCO HOBBS DIVISION PRODUCTION DEPT. JOB: REC. SPECS DRAWING NO: ES-1 SHEET X OF 3	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE:	NONE		